



**DYNASEAL, OIL SEALED, VACUUM PUMP SYSTEMS**

(Medical NFPA 99-C Compliant)

**Available Options**

**Motor Enclosure**

- TEFC (*standard*)
- High Efficiency
- Premium Efficiency
- Other \_\_\_\_\_

**Vacuum Receiver**

- Galvanized
- Epoxy Coated
- Other \_\_\_\_\_

**Systems Options**

- Low Oil Level Switches/Lights
- System Inlet Isolation Valve
- System Inlet Flexible Connectors
- Discharge Flexible Connectors
- Vibration Isolators (*set of 8*)
- Other \_\_\_\_\_

**System Voltage Adder**

- 460 Three Phase, 60Hz. (*standard*)
- 208 Three Phase, 60Hz.  
*Line voltage must be 207V or higher*
- 208 Three Phase, 60Hz.  
*Dedicated 208V (200V) Motor*
- 230 Three Phase, 60Hz.
- 575 Three Phase, 60Hz.
- Other \_\_\_\_\_

**Electrical Options**

**Disconnects**

- Circuit Breakers
- Circuit Breaker Disconnects

**Other Electrical Options**

- Power on Lights
- Remote Panel for Alarm Silence
- Nema Size Starters
- Other \_\_\_\_\_