



OIL MATERIAL SAFETY DATA SHEET
DynaSeal™, ROTARY VANE PUMPS AND SYSTEMS
OIL # 974-015F-A000

PRODUCT INFORMATION:

CHEMICAL NAME: POLYALPHAOLEFIN
CHEMICAL FAMILY: SYNTHETIC HYDROCARBON
FORMULA: C_{10n}H_{20n+2}
CAS #: PROPRIETARY

COMPONENTS AND HAZARD STATEMENT:

NOTE: This product is **NON-HAZARDOUS**. The product contains no known carcinogens. No special warning labels are required under OSHA 29 CFR 1910.1200.

NOTE: this product complies with FDA 21 CFR 178.3570 regarding lubricants for incidental food contact.

SAFE HANDLING AND STORAGE:

NOTE: Do not take internally. Avoid contact with skin, eyes, and clothing. Upon contact with skin, wash with soap and water. Flush eyes with water for 15 minutes and consult physician. Wash contaminated clothing before reuse.

NOTE: Keep container tightly sealed when not in use.

PHYSICAL DATA:

APPEARANCE: CLEAR LIQUID, YELLOW TO LIGHT BROWN TINT
BOILING POINT: >300°F
VAPOR PRESSURE: <0.01mmHg @ 20°C
SPECIFIC GRAVITY (WATER = 1): 0.79-0.85
VOLATILES, PERCENT BY VOLUME: 0%
ODOR: NONE
SOLUBILITY IN WATER: INSOLUBLE
EVAPORATION RATE (BUTYL ACETATE = 1): NIL



OIL MATERIAL SAFETY DATA SHEET
DynaSeal™, ROTARY VANE PUMPS AND SYSTEMS
OIL # 974-015F-A000

FIRE AND EXPLOSION HAZARDS:

FLASH POINT (BY CLEVELAND OPEN CUP): 425°F

FLAMMABLE LIMITS: NOT ESTABLISHED

AUTOIGNITION TEMPRATURE: NO DATA

HMIS RATINGS:

HEALTH: 0

FLAMMABILITY: 1

REACTIVITY: 0

NFPA RATINGS: NOT ESTABLISHED

EXTINGUISHING MEDIA: DRY CHEMICAL: CO₂ FOAM: WATER SPRAY (FOG)

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

NOTE: Burning fluid may evolve irritating/noxious fumes. Firefighters should use NIOSH/MNSA-approved self-contained breathing apparatus. Use water to cool fire exposed containers. Use water carefully near exposed liquid to avoid frothing and splashing of hot liquid.

REACTIVITY DATA:

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

INCOMPATIBLE MATERIALS: STRONG OXIDIZERS

CONDITIONS TO AVOID: EXCESSIVE HEAT

HAZARDOUS DECOMPOSITION PRODUCTS: ANALOGOUS COMPOUNDS EVOLVE CARBON MONOXIDE, CARBON DIOXIDE, AND OTHER UNIDENTIFIED FRAGMENTS WHEN BURNED. SEE SECTION 5.

HEALTH HAZARDS DATA:

THRESHOLD LIMIT VALUE: 5MG/M³ACGIH

SITUATIONS TO AVOID: AVOID BREATHING OIL MISTS

FIRST AID PROCEDURES:

INGESTION: CONSULT A PHYSICIAN AT ONCE. **DO NOT INDUCE VOMITING.**
MAY CAUSE NAUSEA AND DIARRHEA.

INHALATION: PRODUCT IS NOT TOXIC BY INHALATION. IF OIL MIST IS INHALED,
REMOVE TO FRESH AIR AND CONSULT PHYSICIAN.

NOTE: To the best of our knowledge the toxicity of this product had not been fully investigated. Analogous compounds are considered to be essentially non-toxic.



OIL MATERIAL SAFETY DATA SHEET
DynaSeal™, ROTARY VANE PUMPS AND SYSTEMS
OIL # 974-015F-A000

PERSONAL PROTECTION INFORMATION:

RESPIRATORY PROTECTION: USE IN WELL VENTILATED AREA

VENTALATION: LOCAL EXHAUST

PROTECTIVE GLOVES: NOT REQUIRED, BUT RECOMMENDED, ESPECIALLY FOR PROLONGED EXPOSURE.

EYE/FACE PROTECTION: GOGGLES

SPILL OR LEAK PROCEDURES:

NOTE: In case of spill, wear suitable protective equipment, especially goggles. Stop source of spill. Dike spill area. Use absorbent materials to soak up fluid (i.e. sand, sawdust, and commercially available materials). Wash spill area with large amounts of water. Properly dispose of all materials.

WASTE DISPOSAL METHODS:

NOTE: Incinerate this product and all associated wastes in a licensed facility in accordance with Federal, state, and local regulations.

NOTE: The information in this material safety data sheet should be provided to all that use, handle, store, transport, or otherwise exposed to this product. TRAVAINI PUMPS believes the information in this document to be reliable and up to date of publication, but makes no guarantee that it is.

DOC: MATERIAL SAFETY DATA SHEET FOR TRAVAINI, P/N 974-015-A000
FILE: 974015F.DOC
REV: 7/8/97