



DEVARNEX MATERIAL SAFETY DATA SHEET
ROTARY VANE PUMPS AND LIQUID RING COMPRESSORS
#990-0032-A000 & 990-006-A000

PRODUCT INFORMATION:

Specifically formulated synthetic fluid capable of dissolving varnish and solubilizing sludge from lubricating systems while they are operating.

990-0032-A000 & 990-0066-A000 are designed for vane and single acting piston type compressors. It contains oxidation and rust inhibitors, and can be used as a short-term lubricant (up to 400 hours). It is fully compatible with mineral oils and all TRAVAINI lubricants, and is highly recommended for use as a flushing fluid when changing over to TRAVAINI lubricants. Its high flash point and non-toxic nature insure safety in its application. It should not be used in painted crankcases due to its high solvency effect.

APPLICATIONS:

Cleaning fluid for removal of varnish, dirt and oxidized fluid form compressor-lubricating systems.

Flush fluid when changing from other lubricants to TRAVAINI compressor lubricants.

TYPICAL PROPERTIES:

VISCOSITY @40°C, ASTM D-445:	65.9 cs (141 SUS)
@100°C:	7.9 cs (44 SUS)

VISCOSITY INDEX:	81
-------------------------	----

FLASH POINT:	490°F
---------------------	-------

FIRE POINT:	515°F
--------------------	-------

POUR POINT:	-35°F
--------------------	-------

TOTAL ACID NUMBER , MG KOH/G:	<.05
--------------------------------------	------

DENSITY AT 60°F, lbs./gal:	8.03
-----------------------------------	------

*THESE VALUES ARE NOT INTENDED FOR PREPARING SPECIFICATIONS.

