

TCD 80 Self-Cooling Centrifugal Pump



200 Newsome Drive
Yorktown, VA 23693
1-800-535-4243
www.Travaini.com



Head Capacity	20 to 460 Feet
Capacity	Up to 1200 USGPM
Features	Specially designed cooling fins allow handling of fluids up to 608 °F
Shaft Sealing	Single mechanical seal
Options	Bareshaft Pump Coupled to electric motor
Temperature	Up to 608 F (320 C)
Casing Pressure	232 PSI to 248 F; 150 PSI to 608 F
Viscosity	Up to 1400 SSU

Technical Data

PUMP TYPE		TCD80-160		TCD80-200		TCD80-250	
Head, max	Ft	50	200	72	317	115	460
Capacity, max	GPM	550	1100	600	1170	800	1200
Speed	RPM	1750	3500	1750	3500	1750	3500
Max. Inlet pressure	PSIG	110	110	110	110	110	110

Standard Materials of Construction**

Part No.	Description	GA	A3
102	Volute Casing	Ductile Iron	Stainless Steel AISI 316
163	Casing Cover		
167	Cooling Plate		
210	Shaft	Stainless Steel AISI 420	
230	Impeller	Cast iron	
330	Bearing Housing		
433.2	Mechanical Seal	Ni-Resist/ Carbon/Viton	S.S AISI 316/ Carbon/Viton
502	Wear Ring	Carbon steel	S.S AISI 316

Model Designation

TCD80-250 A/2-R/GA	
T	Travaini manufacturer
C	Monostage centrifugal pump
D	Self-cooling centrifugal pump
80	Discharge flange size (mm)
250	Nominal diameter of impeller (mm)
A	Modification of hydraulic design
2—R	Constructive design number— Single mechanical seal
GA	Materials of construction (See table)

**Special Materials Available Upon Request

--For further information please consult Travaini Pumps USA.

REF:	JM/RR	Date	6/30/2017	No:	101024.000
------	-------	------	-----------	-----	------------