

# TCHM 150 Centrifugal Pump



200 Newsome Drive  
Yorktown, VA 23693  
1-800-535-4243  
www.Travaini.com



<b>Head Capacity</b>	25 to 105 Feet
<b>Capacity</b>	Up to 2600 USGPM
<b>Features</b>	Closed impeller design for use with clean or muddy liquids
<b>Shaft Sealing</b>	Mechanical seal (standard) Double mechanical seal Packed Stuffing box
<b>Options</b>	Bareshaft Pump Coupled to electric motor Monoblock
<b>Temperature</b>	GS & RA: -20°C-280°C A3, HC, & DU: -40°C-280°C

## Technical Data

PUMP TYPE		TCHM150-250
Head, max	Ft	105
Capacity, max	GPM	2600
Speed	RPM	1750

## Standard Materials of Construction\*\*

Part No.	Description	GS	RA	A3	HC	DU
102	Pump casing	Ductile iron			Hastealloy C	ASTM-CN7M
135	Wear plates	-	Cast iron			
161	Casing cover	Ductile iron				
210	Shaft	Stainless steel AISI 316				Incoloy 825
230	Impeller					ASTM-CN7M
330	Bearing housing	Cast iron				
524	Shaft sleeve	Stainless steel AISI 316		Hastealloy C	Incoloy 825	

## Model Designation

<b>TCHM150-250 A/1X-C/A3</b>	
T	Travaini manufacturer
C	Monostage centrifugal pump
H	Closed impeller
M	Monoblock Construction
150	Discharge flange size (mm)
250	Nominal diameter of impeller (mm)
A	Modification of hydraulic design
1X	Constructive project number
C	Shaft Sealing: C—single mechanical seal 2C— Double mechanical seal
A3	Materials of construction

\*\*Special Materials Available Upon Request

--For further information please consult Travaini Pumps USA.