

# TCH 25 Centrifugal Pump



200 Newsome Drive  
Yorktown, VA 23693  
1-800-535-4243  
www.Travaini.com



<b>Head Capacity</b>	5 to 320 Feet
<b>Capacity</b>	Up to 65 USGPM
<b>Features</b>	Oversized alloy shaft to minimize deflection and vibrations
<b>Shaft Sealing</b>	Mechanical seal (standard) Double mechanical seal Packed stuffing box
<b>Options</b>	Bareshaft pump Coupled to electric motor Monoblock
<b>Temperature</b>	GS & RA: -20°C-280°C A3, HC, & DU: -40°C-280°C

## Technical Data

PUMP TYPE		TCH25-125		TCH25-160		TCH25-200	
Head, max	Ft	31	122	52	214	75	330
Capacity, max	GPM	25	42	25	42	32	65
Speed	RPM	1750	3500	1750	3500	1750	3500

## Standard Materials of Construction\*\*

Part No.	Description	GS	RA	A3	HC	DU
102	Pump casing	Ductile iron			Hastealloy C	ASTM-CN7M
135	Wear plates	-	Cast iron			
161	Casing cover	Ductile iron				
210	Shaft	Stainless steel AISI 316			Incoloy 825	
230	Impeller				ASTM-CN7M	
330	Bearing housing	Cast iron				
524	Shaft sleeve	Stainless steel AISI 316		Hastealloy C	Incoloy 825	

## Model Designation

TCH25-200 A/1X-C/A3	
T	Travaini manufacturer
C	Monostage centrifugal pump
H	Closed impeller
25	Discharge flange size (mm)
200	Nominal diameter of impeller (mm)
A	Modification of hydraulic design
1X	Constructive project number
C	Shaft sealing: C—Single mechanical seal 2C— Double mechanical seal
A3	Materials of construction

\*\*Special materials available upon request

--For further information please consult Travaini Pumps USA.

REF:	JGJ/RR	Date	3/17/2015	No:	100288.000
------	--------	------	-----------	-----	------------